

INSTALLATIEVOORSCHRIFTEN EN GEBRUIKSAANWIJZING
INSTALLATION INSTRUCTIONS AND OPERATING MANUAL
INSTALLATION ET MODE D'EMPLOI
EINBAUANLEITUNG UND GEBRAUCHSANWEISUNG
INSTRUCCIONES DE INSTALACIÓN Y USO
REQUISITI PER L'INSTALLAZIONE E ISTRUZIONI PER L'USO
MONTERINGS- OG BRUKSANVISNING

HOUTKACHEL
WOOD STOVE
POELE A BOIS
HOLZ-FEUERSTÄTTE
ESTUFA DE LEÑA
STUFA A LEGNA
ILDSTED



BRUT



Table of contents

| | |
|---|-----------|
| Introduction | 3 |
| Performance declaration | 4 |
| Safety | 6 |
| Installation requirements | 6 |
| General | 6 |
| Flue | 6 |
| Room ventilation | 7 |
| Floor and walls | 7 |
| Product description | 8 |
| Installation | 8 |
| General preparation | 8 |
| Installing and connecting | 9 |
| Use | 9 |
| First use | 9 |
| Fuel | 9 |
| Lighting | 10 |
| Burning wood | 11 |
| Controlling combustion air | 12 |
| Extinguishing the fire | 12 |
| Removing ash | 12 |
| Fog and mist | 12 |
| Resolving problems | 12 |
| Maintenance | 12 |
| Flue | 13 |
| Cleaning and other regularly maintenance | 13 |
| Spares BRUT | 14 |
| Appendix 1: Technical data | 15 |
| Appendix 2: Dimensions | 16 |
| Appendix 3: Distance from combustible material | 17 |
| Appendix 4: Diagnosis diagram | 19 |
| Index | 20 |



Introduction

Dear user,

By purchasing this heating appliance from DOVRE you have selected a quality product. This product is part of a new generation of energy-efficient and environmentally-friendly heating appliances. These stoves make optimum use of convection heat as well as thermal radiation (radiant heat).

- ▶ Your DOVRE appliance has been manufactured with state-of-the-art production equipment. In the unlikely event of a malfunction, you can always rely on DOVRE for support and service.
- ▶ The appliance should not be modified; please always use original parts.
- ▶ The appliance is intended for use in a living room. It must be hermetically connected to a properly working flue.
- ▶ We advise you have the appliance installed by an authorized and competent installer.
- ▶ DOVRE cannot be held liable for any problems or damage resulting from incorrect installation.
- ▶ Observe the following safety regulations when installing and using the appliance.

In this manual, you can read how the DOVRE heating appliance can be installed, used and maintained safely. Should you require additional information or technical data, or should you experience an installation problem, please first contact your supplier.

© 2015 DOVRE NV



Performance declaration

In accordance with construction products regulation 305/2011

No. 045-CPR-2015

1. Unique identification code of the product type:

BRUT

2. Type, batch or serial number or other form of identification for the construction product, as prescribed in article 11, subsection 4:

Unique serial number.

3. Intended use for the construction product, in accordance with the applicable harmonised technical specification, as specified by the producer:

Stove for solid fuel without production of warm water in accordance with EN 13240.

4. Name, registered trade name or registered trademark and contact address of the producer, as prescribed in article 11, subsection 5:

Dovre N.V. Nijverheidsstraat 18 2381 Weelde Belgium.

5. If applicable, name and contact address for the authorised whose mandate covers the tasks specified in article 12, subsection 2:

-

6. The system or systems for the assessment and verification of the performance durability of the construction product, specified in appendix V:

System 3

7. If the performance declaration refers to a construction product that falls under a harmonised standard:

The appointed agency KVBG, registered under number 2013, has performed a type test under system 3 and has issued the test report No. 2015/0033.

8. If the performance declaration concerns a construction product for which a European technical assessment is issued:

-



9. Declared performance:

| | |
|--|--|
| The harmonised norm | EN 13240:2001/A2 ;2004/AC :2007 |
| Essential characteristics | Performance Wood |
| Fire safety | |
| Fire resistance | A1 |
| Distance from combustible material | Minimum distance in mm Rear: 400 Side: 400 |
| Risk of glowing particles falling out | Conform |
| Emission of combustion products | CO: 0.04% (13%O ₂) |
| Surface temperature | Conform |
| Electrical safety | - |
| Ease of cleaning | Conform |
| Maximum operating pressure | - |
| Flue gas temperature at nominal output | 293 °C |
| Mechanical resistance (carrying weight of chimney) | Not determined |
| Nominal output | 6.5 kW |
| Efficiency | 78 % |

10. The performance of the product described in points 1 and 2 conform with the performance reported in point 9.

This performance declaration is supplied under the exclusive responsibility of the producer specified in point 4:

T. Gehem



Tom Gehem
CEO

01/03/2015 Weelde

Due to continuous product improvement, the supplied appliance specifications may vary from the description in this brochure without prior notice having been given.

DOVRE N.V.

Nijverheidsstraat 18 Tel : +32 (0) 14 65 91 91

B-2381 Weelde Fax : +32 (0) 14 65 90 09

Belgium E-mail : info@dovre.be



Safety

-  Please note: All safety regulations must be complied with strictly.
-  Please read carefully the instructions supplied with the appliance for installation, use and maintenance before using the appliance.
-  The appliance must be installed in accordance with the legislation and requirements applicable in your country.
-  All local regulations and the regulations relating to national and European standards must be observed when installing the appliance.
-  The appliance should preferably be installed by an authorised installer. Installers will be aware of the applicable regulations and requirements.
-  The appliance is designed for heating purposes. All surfaces, including the glass and connecting tube, can become very hot (over 100°C)! When operating, use a so-called "cold hand" or an oven glove.
-  Ensure that the appliance is adequately guarded if young children, disabled people, the elderly or animals are present in the vicinity.
-  Safety distances from flammable materials must be strictly adhered to.
-  Do not place any curtains, clothes, laundry or other combustible materials on or near the appliance.
-  When in use, do not use flammable or explosive substances in the vicinity of the appliance.
-  Avoid chimney fires by having the chimney swept regularly. Never burn wood with the door open.
-  In the event of a chimney fire: close all the appliance's air inlets and alert the fire service.
-  If the glass in the appliance is broken or cracked, it must be replaced before the stove is used again.
-  Do not exert force on the door, do not allow children to pull on the opened door, never stand or

sit on the opened door and do not place heavy objects on the door.

-  Ensure that there is adequate ventilation in the room in which the appliance is installed. If ventilation is insufficient, combustion will be incomplete whereby toxic gases can spread through the room. See the chapter "Installation requirements" for more information on ventilation.

Installation requirements

General

- ▶ The appliance must be connected tightly to a well-functioning flue.
- ▶ For connection measurements: see "Technical data" appendix.
- ▶ Ask the fire service and/or your insurance company about any specific requirements and regulations.

Flue

The flue is needed for:

- ▶ Removal of combustion gases via natural draught.
 -  As the warm air in the flue or chimney is lighter than the outside air, it rises.
- ▶ Air intake, needed for the combustion of fuel in the appliance.

A poorly-functioning flue or chimney can cause smoke to escape into the room when the door is opened. Damage caused by smoke emissions into the room is not covered by the warranty.

-  Do not connect multiple appliances (such as a boiler for central heating) to the same flue, unless local or national regulations allow this. In the event of two connections ensure that the difference in height between the connections is no less than 200 mm.

Ask your installer for advice regarding the flue. Refer to the European norm EN 13384 for a correct calculation for the flue.



The flue must satisfy the following **requirements**:


- ▶ The flue or chimney must be made of fire-resistant material, preferably ceramics or stainless steel.
- ▶ The flue or chimney must be airtight and well-cleaned and guarantee sufficient draught.

i A draught/vacuum of 15 - 20 Pa during normal operation is ideal.

- ▶ Starting from the flue spigot, the flue must run as vertically as possible. Changes in direction and horizontal pieces disrupt the outward flow of combustion gases and may cause soot deposits.
- ▶ To prevent combustion gases from cooling down too much, which reduces the draught, ensure that the interior diameter is not too big.
- ▶ The flue or chimney should ideally have the same diameter as the connection collar.

i For nominal diameter: see "Technical data" appendix. If the smoke channel is well insulated, the diameter may be slightly bigger (up to 2x the section of the connection collar).

- ▶ The section (area) of the smoke channel must be constant. Wider segments and (in particular) narrower segments disrupt the outward flow of combustion gases.
- ▶ In fitting a cover plate/exhaust cap to the flue: make sure that the cover does not restrict the flue outlet and that the cap does not impede the outward flow of combustion gases.
- ▶ The flue must end in a zone that is not affected by surrounding buildings, trees or other obstacles.
- ▶ The flue outside the house must be insulated.
- ▶ The flue should be at least 4 metres high.
- ▶ As a rule of thumb: 60 cm above the ridge of the roof.
- ▶ If the ridge of the roof is more than 3 metres from the flue: use the measurements given in the following figure. A = the highest point of the roof within a distance of 3 metres.



Room ventilation

For good combustion, the appliance needs air (oxygen). This air is supplied via adjustable air inlets from the area in which the appliance is installed.

- ⚠ If ventilation is insufficient, combustion will be incomplete, which may lead toxic gases to spread through the room.

As a rule of thumb, the air supply should be 5.5 cm²/kW. Extra ventilation is needed when:

- ▶ The appliance is in a well-insulated area.
- ▶ There is mechanical ventilation, for example, a central extraction system or an extraction hood in an open kitchen.

You can provide extra ventilation by having a ventilation louvre fitted on the outside wall.

Make sure that other air consuming appliances (such as tumble-driers, other heating appliances or a bathroom fan) have their own supply of outside air, or are switched off when you use the appliance.


Floor and walls

The floor on which the appliance is placed must have sufficient bearing capacity. The weight of the appliance is given in the appendix "Technical Data appendix".

- ⚠ Protect flammable flooring from heat radiation by means of a fireproof protective plate. See the appendix "Distance from combustible material".
- ⚠ Remove combustible material such as linoleum, carpets/rugs and similar materials below the fireproof protective plate.

-  Keep sufficient distance between the appliance and combustible materials such as wooden walls and furniture.
-  The connecting tube also radiates heat. Ensure that there is sufficient distance or a shield between the connecting tube and combustible material.
The rule of thumb for a single-walled tube is a distance of 3x the diameter. If a lining shell is fitted around the tube, a distance of 1x the diameter is permissible.
-  Carpets and rugs must be at least 80 cm away from the fire.
-  Use a fireproof floor plate to protect a flammable floor from any ash which may fall in front of the stove. The floor plate must comply with national standards.
-  For the dimensions of the fireproof protective plate: see the appendix "Distance from combustible material".
-  For further requirements with respect to fire safety, see the appendix "Distance from combustible material".

Product description



1. Connection collar
2. Door
3. Latch
4. Primary air control
5. Secondary air control (glass wash)


Door lock

The appliance is supplied with the latch installed. Open the door by turning the latch outwards. As the latch becomes hot during use, a glove has been supplied which you can use to protect your hand.


Installation

General preparation

- ▶ Please check the appliance immediately after delivery for damage during transport or any other damage or defects. The appliance is attached to the pallet with screws at the bottom.
-  If you detect transport damage or any other damage or defects, do not use the appliance and notify the supplier.
- ▶ Remove removable parts (fire-resistant inner plates, fire grate, ashtray) from the stove before starting installation.
-  It is easier to move the appliance and to avoid damage if the removable parts have been removed.
-  Note the location of the removable parts, so that you can re-position the parts in the correct place later on.




1. Open the door; see the following figure:



2. Remove the fire-resistant inner plates; see the following figure:
 - a. First remove the baffle plate.
 - b. Remove the grate and the ash pan (1) and (3).

i Vermiculite inner plates are light and tend to be ochrous in colour on delivery. They insulate the combustion chamber to boost combustion.



Removable internal parts

- 1 fire compartment base
- 2 baffle plate
- 3 ash pan
- 4 side inner plate left
- 5 side inner plate right
- 6 rear inner plate

Installing and connecting

1. Position the appliance in the correct place, and make sure it is level.
2. Connect the appliance to the flue hermetically.
3. Re-position all removed parts in the correct places in the appliance.

! Never use the appliance without the fire-resistant inner plates.

The appliance is now ready for use.

Use

First use

When you use the appliance for the first time, make an intense fire and keep it going for a good few hours. This will cure the heat-resistant paint finish. This may result in some smoke and odours. You could open windows and doors for a while in the area in which the appliance is located.

Fuel

This appliance is only suitable for burning natural wood; sawn and chopped wood that is sufficiently dry.

Do not use other fuels, as they can cause serious damage to the appliance.

The following fuels may not be used as they pollute the environment, and because they heavily pollute the appliance and flue, which may lead to a chimney fire:

- ▶ Treated wood, such as scrap wood, painted wood, impregnated wood, preserved wood, plywood and chipboard.
- ▶ Plastics, scrap paper and domestic waste.

Wood

- ▶ Hardwood, such as oak, beech, birch and fruit tree wood is the ideal fuel for your stove. This type of wood burns slowly with calm flames. Softwood contains more resins, burns faster and sparks more.
- ▶ Use seasoned wood that contains no more than 20% moisture. The wood should have been seasoned for at least 2 years. Wood with a




moisture content of 20% provides 4.2 kWh per kg wood. Wood with a moisture content of 15% provides 4.4 kWh per kg wood. Freshly felled wood has a moisture content of 60% and only provides 1.6 kWh per kg wood.

- ▶ Saw the wood to size and split it while it is still fresh. Fresh wood is easier to split, and split wood dries more easily. Store the wood under a roof where the wind has free access.
- ▶ Do not use damp wood. Damp logs do not produce heat as all the energy is used in the evaporation of moisture. This will result in a lot of smoke and soot deposits on the appliance door and in the flue. The water vapour will condense in the appliance and can leak away through chinks in the stove, causing black stains on the floor. It may also condense in the chimney and form creosote. Creosote is a highly flammable compound and may cause a chimney fire.


Lighting

You can check whether the flue has sufficient draught by lighting a ball of paper above the baffle plate. A cold flue often has insufficient draught and consequently, some smoke may escape into the room instead of up the chimney. You can avoid this problem by lighting the fire as described below.

1. Stack two layers of medium sized logs crosswise.
2. Stack two to three layers of kindling crosswise on top of the logs.
3. Place a firelighter between the bottom layer of kindling and light the firelighter according to the instructions on the packaging.



4. Close the appliance door and open the primary and secondary air inlets; see the following figure.
5. Allow the fire develop into a good blaze until there is a glowing bed of charcoal. You can then add fuel and adjust the appliance, see the chapter "Stoking with wood".



Secondary air slide

- A Open entirely
- B Half open
- C Closed entirely

Primary air slide

- D Open entirely
- E Half open
- F Closed entirely

Maximum amount of wood

To stoke continuously at the rated power, wood must be added every 45 minutes. If you use a smaller amount of wood each time, you can add wood more often. Each stove is designed to work with a specific maximum amount of wood. If you use a larger quantity of wood, the heat output increases. This can cause the hearth to be overloaded and parts can be damaged.

Allowable maximum amount of fuel when using wood with a moisture content of 15%:


- ▶ BRUT can be filled with a maximum of 1.5 kg wood every 45 minutes.

- ⚠ Do not fill the combustion chamber more than one third full, and never stack wood above the openings for secondary air.


Burning wood

After you have followed the instructions for lighting:

1. Slowly open the door of the appliance.
2. Spread the charcoal evenly across the bottom of the stove base.
3. Stack a few logs on the charcoal.

Open stacking

If the logs are stacked openly, the wood will burn quickly as the oxygen can reach each log easily. If you want to use the stove for a short while, make an open stack.

Compact stacking

If the logs are stacked tightly, the wood will burn more slowly as the oxygen can only reach some logs easily. If you want to burn wood for a longer period, make a compact stack.


4. Close the door of the appliance.
5. Close the primary air inlet and leave the secondary air inlet open.

- ⚠ Do not fill the appliance by more than a third.



Controlling combustion air

The appliance has various features for air control; see next figure.



The primary air inlet regulates the air under the grate (1).

The secondary air inlet regulates the air for the glass (air wash) (2).

The back wall has permanent vents (3) below the baffle plate that allow for post-combustion.

Advice

-  Never burn wood with an open door.
-  Regularly burn wood with intense roaring fires.

If you burn at a low setting frequently, tar and creosote may be deposited in the flue. Tar and creosote are highly combustible substances. Thicker layers of these substances may catch fire if the temperature in the flue increases suddenly. By allowing the fire to burn very intensely regularly, layers of tar and creosote will disappear.

Low intensity fires can also cause tar deposits on the stove window and door.

When the outside temperature is mild, it is better to burn wood intensely for a few hours instead of having a low intensity fire for a long period of time.

- ▶ Control the air supply using the air vent.



The air inlet not only supplies air to the fire but to the glass as well, so that it does not quickly become dirty.

- ▶ Open the primary air inlet for the time being if the air supply by the secondary air inlet is inadequate or if you want to fan the fire.
- ▶ Topping up with a few logs regularly is better than adding many logs in one go.

Extinguishing the fire

Do not add fuel and just let the fire go out. If a fire is damped down by reducing the air supply, harmful substances will be released. For this reason, the fire should be allowed to go out naturally. Keep an eye on the fire until it has gone out. All air inlets can be closed once the fire has died completely.

Removing ash

After wood has been burnt, a relatively small amount of ash remains. This ash bed is a good insulating layer for the stove base plate and improves combustion. It is a good idea to leave a thin layer of ash on the stove base plate.

The flow of air through the fire plate must not be obstructed, however, and no ash may be allowed to accumulate behind a cast-iron inner plate. Remove the excess ash regularly.

Using the glove supplied, remove the ash pan and empty it. Replace the ash pan and close the door.

Fog and mist

Fog and mist hinder the flow of flue gases through the flue. Smoke can blow back and cause a stench. If it is not strictly necessary, it is better not to use the stove in foggy and misty weather.

Resolving problems

Refer to the appendix "Diagnostic diagram" to resolve any problems in using the appliance.

Maintenance

Follow the maintenance instructions in this chapter to keep the appliance in good condition.



Flue

In many countries, you are required by law to have your chimney checked and maintained.

- ▶ At the start of the heating season: have the chimney swept by a recognised chimney sweep.
- ▶ During the heating season and after the chimney has not been used for a long time: have the chimney checked for soot.
- ▶ At the end of the heating season: close off the chimney and plug with newspaper.

Cleaning and other regularly maintenance

 Do not clean the appliance when it is still warm.

- ▶ Clean the exterior of the appliance with a dry lint-free cloth.

You can clean the appliance interior thoroughly at the end of the heating season:

- ▶ If necessary, first remove the fire-resistant inner plates. See the chapter "Installation" for instructions on removing and installing the inner plates.
- ▶ If necessary, clean the air supply ducts.
- ▶ Remove the baffle plate at the top of the appliance and clean it.

Checking fire-resistant inner plates

The fire-resistant inner plates are consumables that are subject to wear and tear. Vermiculite inner plates are fragile. Do not knock the inner plates with logs. Check the fire-resistant inner plates frequently and replace them when necessary.

- ▶ See the chapter "Installation" for instructions on removing and installing the inner plates.

 The insulating vermiculite or chamotte inner plates may develop hairline cracks, but this does not affect their performance adversely.

 Cast-iron inner plates last a long time if you remove frequently the ash that can accumulate behind them. If accumulated ash behind the cast-iron plate is not removed, the plate will no

longer be able to dissipate the heat to the surroundings and this may cause the plate to warp or crack.

 Never use the appliance without the fire-resistant inner plates.

Cleaning the glass

Dirt clings less easily to well-cleaned glass. Proceed as follows:

1. Remove dust and loose soot with a dry cloth.
2. Clean the glass with stove glass cleaner:
 - a. Apply stove glass cleaner to a kitchen sponge, rub down the entire glass surface and give the cleaning agent time to react.
 - b. Remove the dirt with a moist cloth or kitchen tissue.
3. Clean the glass again with a normal glass cleaning product.
4. Rub the glass clean with a dry cloth or kitchen tissue.

▶ Do not use abrasive or aggressive products to clean the glass.

▶ Wear household gloves to protect your hands.

 If the glass in the appliance is broken or cracked, it must be replaced before you can use appliance again.

 Ensure that no stove glass cleaner runs between the glass and the cast-iron door.

Lubrication

Although cast-iron is slightly self-lubricating, you will still need to lubricate moving parts frequently.

- ▶ Lubricate the moving parts (such as guide systems, hinge pins, latches and air slides) with heat resistant grease that is available in the specialist trade.

Checking the seal

- ▶ Check whether the door sealing rope is still in good condition and works well. The sealing rope is subject to wear and will need to be replaced over time.



- ▶ Check the appliance for air leaks. Close any chinks with stove sealant.

⚠ Allow the sealant to harden fully before lighting the appliance, as any moisture in the sealant will form bubbles, resulting in a new air leak.


Replacing the glass

⚠ If the glass in the appliance is broken or cracked, it must be replaced before the stove is used again.

Proceed as follows:

1. Unscrew the glass fixings and remove the glass.
2. Check the glass seal and, if necessary, fit a new sealing rope.
3. Place the new glass in the groove and tighten the glass fixings.

Spares BRUT



| Pos. | Part number | Description | Quantity |
|------|--------------|------------------------|----------|
| 01 | 03.66555.000 | fire compartment base | 1 |
| 02 | 03.76189.000 | baffle plate | 1 |
| 03 | 03.05216.000 | ash pan | 1 |
| 04 | 03.77566.000 | side inner plate left | 1 |
| 05 | 03.77567.000 | side inner plate right | 1 |
| 06 | 03.77565.000 | rear inner plate | 1 |




Appendix 1: Technical data

| Model | BRUT |
|--|-----------------------|
| Nominal output | 6.5 kW |
| Flue connection (diameter) | 150 mm |
| Weight | 105 kg |
| Recommended fuel | Wood |
| Fuel property, max. length | 35 cm |
| Mass flow of flue gasses | 7.1 g/s |
| Flue gas temperature measured in the measurement section | 293 °C |
| Temperature measured at appliance exit | 327 °C |
| Minimum draught | 12 Pa |
| CO emission (13%O ₂) | 0.04 % |
| NOx emission (13% O ₂) | 92 mg/Nm ³ |
| CnHm emission (13%O ₂) | 57 mg/Nm ³ |
| Particulate emission | 18 mg/Nm ³ |
| Particulate emission in accordance with NS3058-NS3059 | - |
| Efficiency | 78 % |


Appendix 2: Dimensions

BRUT




Appendix 3: Distance from combustible material

BRUT



| | |
|---|--|
| 1 | Combustible material |
| 2 | Incombustible material, thickness 100 mm |

BRUT - Dimensions of fireproof floor plate



Minimum dimensions of fireproof floor plate

| | A (mm) | B (mm) |
|-----------|--------|--------|
| Din 18891 | 500 | 300 |
| Germany | 500 | 300 |
| Finland | 400 | 100 |
| Norway | 300 | 20 |

Appendix 4: Diagnosis diagram

| | | | | | Problem | |
|---|---|---|---|---|--|---|
| ● | | | | | Wood will not stay lit | |
| | ● | | | | Gives off insufficient heat | |
| | | ● | | | Smoke emissions into the room when adding wood | |
| | | | ● | | Fire in appliance is too intense, is hard to adjust | |
| | | | | ● | Deposit on the glass | |
| | | | | | possible cause | possible solution |
| ● | ● | ● | | ● | Insufficient draught | A cold flue usually fails to create sufficient draught. Follow the instructions for starting a fire in the 'Use' section; open a window. |
| ● | ● | ● | | ● | Wood too damp | Use wood with no more than 20% moisture. |
| ● | ● | ● | | ● | Logs too large | Use small pieces of kindling. Use split logs no larger than 30 cm in circumference. |
| ● | ● | ● | ● | ● | Wood stacked incorrectly | Stack the logs in a way that allows adequate air flow between the logs (open stacking, see "Burning wood") |
| ● | ● | ● | | ● | Flue does not work properly | Check whether the chimney meets the requirements: at least 4 metres high, correct diameter, well-insulated, smooth inside, not too many bends, no obstructions in chimney (bird's nest, too much soot deposit), hermetically tight (no chinks). |
| ● | ● | ● | | ● | Chimney stack incorrect | Sufficiently high above the roof, no obstacles in the vicinity |
| ● | ● | ● | ● | ● | Air inlets set incorrectly | Open the air inlets completely. |
| ● | ● | ● | | ● | Appliance connected to the flue incorrectly | Connection should be hermetically tight. |
| ● | ● | ● | | ● | Vacuum in area in which the appliance is installed | Switch off extraction systems. |
| ● | ● | ● | | ● | Insufficient supply of fresh air | Provide an adequate air supply; if necessary use outside air connection. |
| ● | ● | ● | | ● | Bad weather ? Inversion (reversed air flow in chimney because of a high outside temperature), extreme wind speeds | We recommend you don't use the appliance in the case of inversion. If required, install an extra hood on the flue to increase the draught. |
| | | ● | | | Draught in the living room | Avoid draught in the living room, do not place the appliance near a door or heating air ducts. |
| | | | | ● | Flames touch the glass | Make sure the wood is not positioned too close to the glass. Slide the primary air inlet cover closer to the "Closed" position. |
| | | | ● | | Appliance is leaking air | Check the door seals and appliance joints. |

Index

| A | |
|--|----|
| Adding wood | |
| smoking appliance | 19 |
| Adverse weather conditions, do not burn wood | 12 |
| Aerating the fire | 12 |
| Air combustion control | 12 |
| Air control | 12 |
| Air inlets | 10 |
| Air leak | 13 |
| ash | 12 |
| Ashes | |
| remove | 12 |
| B | |
| Bearing capacity of floor | 7 |
| Burning | 11 |
| adding fuel | 11 |
| appliance is hard to adjust | 19 |
| fire is too intense | 19 |
| insufficient heat | 19 |
| topping up fuel | 12 |
| Burning wood | |
| insufficient heat | 12 |
| C | |
| Cap on the flue | 7 |
| Carpet | 7 |
| Cast iron inner plates | 9 |
| warning | 9 |
| Chinks in appliance | 13 |
| Cleaning | |
| appliance | 13 |
| glass | 13 |
| Combustible material | |
| distance from | 17 |
| Connecting | |
| dimensions | 16 |
| Controlling air supply | 12 |
| Creosote | 12 |
| D | |
| Damage | 8 |
| Damp wood | 9 |

| Dimensions | 16 |
|------------------------------------|-------|
| Door | |
| opening | 8 |
| sealing rope | 13 |
| Draught | 15 |
| Drying wood | 9 |
| E | |
| Efficiency | 5, 15 |
| External air supply | |
| connecting to | 9 |
| Extinguishing the fire | 12 |
| F | |
| Filling level of the appliance | 11 |
| Fire | |
| extinguishing | 12 |
| kindle | |
| Lighting | 10 |
| Fire-resistant inner plates | |
| maintenance | 13 |
| remove | 9 |
| warning | 9 |
| Fire safety | |
| distance from combustible material | 17 |
| floor | 7 |
| furniture | 7 |
| walls | 7 |
| Floors | |
| bearing capacity | 7 |
| fire safety | 7 |
| Flue | |
| connecting to | 9 |
| connection diameter | 15 |
| height | 7 |
| maintenance | 13 |
| requirements | 7 |
| Flue cap | 7 |
| Flue gas | |
| temperature | 5, 15 |
| Flue gasses | |
| mass flow | 15 |
| Fog, do not burn wood | 12 |
| Fuel | |
| adding | 11 |
| necessary amount | 12 |



| | |
|------------------|----|
| suitable | 9 |
| topping up | 12 |
| unsuitable | 9 |
| wood | 9 |

G

| | |
|---------------------|----|
| Glass | |
| cleaning | 13 |
| cracked | 14 |
| deposit | 19 |
| replacing | 14 |
| Glass damaged | 14 |

H

| | |
|--------------------------|--------|
| Heat, insufficient | 12, 19 |
|--------------------------|--------|

I

| | |
|------------------------------|----|
| Inner plate | |
| vermiculite | 9 |
| Inner plates, fire-resistant | |
| remove | 9 |
| Installing | |
| dimensions | 16 |

K

| | |
|----------------|----|
| Kindling | 19 |
|----------------|----|

L

| | |
|---------------------|----|
| Lighting fire | 10 |
| Lubricant | 13 |
| Lubricate | 13 |

M

| | |
|-----------------------------------|----|
| Maintenance | |
| Clean appliance | 13 |
| cleaning the glass | 13 |
| Fire-resistant inner plates | 13 |
| flue | 13 |
| lubrication | 13 |
| sealing | 13 |
| Mist, do not burn wood | 12 |

N

| | |
|----------------------|--------|
| Nominal output | 12, 15 |
|----------------------|--------|

O

| | |
|------------|---|
| Opening | |
| door | 8 |

P

| | |
|------------------|---|
| Paint | |
| Smoke | |
| during first use | 9 |

| | |
|-------------------------------|----|
| Particulate emission | 15 |
| Parts, removable | 8 |
| Preventing chimney fire | 12 |
| Primary air inlet | 10 |

R

| | |
|-----------------------------------|----|
| Removable parts | 8 |
| Remove | |
| fire-resistant inner plates | 9 |
| Removing ash | 12 |
| Replacing | |
| glass | 14 |

S

| | |
|-------------------------------------|--------|
| Screens | |
| deposit | 19 |
| Sealing rope for door | 13 |
| Secondary air inlet | 10 |
| Smoke emissions into the room | 6 |
| Smoking appliance | 19 |
| Softwood | 9 |
| Solving problems | 12, 19 |
| Stacking logs | 11 |
| Storing wood | 9 |
| Stove glass cleaner | 13 |
| Suitable fuel | 9 |
| Sweeping flue | 13 |

T

| | |
|----------------------------|----|
| Tar | 12 |
| Temperature | 15 |
| Topping up with fuel | 12 |

U

| | |
|-----------------------|---|
| Unsuitable fuel | 9 |
|-----------------------|---|

V

| | |
|--------------------------|---|
| Ventilation | 7 |
| rule of thumb | 7 |
| Ventilation louvre | 7 |



| | |
|--------------------------------|---|
| Vermiculite | |
| fire-resistant | 9 |
| Vermiculite inner plates | 9 |

W

| | |
|--|----------|
| Walls | |
| fire safety | 7 |
| Warning | |
| cast iron inner plates | 9 |
| chimney fire | 9, 12 |
| chimney fires | 6 |
| fire-resistant inner plates | 9 |
| flammable materials | 6 |
| glass broken or cracked | 6, 13-14 |
| hot surface | 6 |
| placing a load on door | 6 |
| requirements | 6 |
| stove glass cleaner | 13 |
| terms and conditions for insurance | 6 |
| ventilation | 6-7 |
| Weight | 15 |
| Wood | 9 |
| damp | 9 |
| drying | 9 |
| right sort | 9 |
| storing | 9 |
| will not stay lit | 19 |

